



RS-2

Powerful vertical reciprocation

Lab Companion Funnel Shaker

- › Enhanced mixing efficiency through double sided vertical reciprocation and adjustable tilt (up to 20°).
- › Convenient one touch funnel installation and removal.
- › Stable center of gravity design for low vibration and noise.


Lab Companion Funnel Shaker (Model: RS-2)

The separation funnel is used during solute solvation or solvent extraction with emission of gas products. The Lab Companion separatory funnel shaker not only allows vertical reciprocation but tilted reciprocation at a 20° angle for more efficient mixing in the separation funnel.



High mixing efficiency and enhanced durability

- Vertical reciprocation at a maximum of 300 rpm and 40 mm stroke length.
- Adjustable shake tilt to achieve high mixing efficiency at low rpm.
- Use of BLDC motor provides outstanding durability, lower noise level, and enhanced stability compared to competitor products using DC motors.



Vertical reciprocation suitable for sample mixing in funnel.



Tilt angle adjustment from 0 to 20° for maximum mixing efficiency.

Simultaneous mixing of up to 4 * 2L funnels

- Fits cone or cylindrical type funnels of up to 2L capacity (capacity limit for previous model was 1L).
- Simultaneous installation of up to 10 * <0.5L funnels, 6 * 0.5-1L funnels, and 4 * 2L funnels (2 double sided holders provided in basic set).

Maximum number of installed funnels (per side)

Funnel capacity	Round type	Cylindrical type
Less than 500 mℓ	3-5ea	3-5ea
500 mℓ	3ea	3ea
1L	3ea	3ea
2L	2ea	2ea

Accessories

Cat. No.	Description
AAA32502	Funnel holder

*Funnels are not provided.



Up to 5 holders may be installed on each side.

Easy sample installation and removal; stable operation


- One-touch mechanism for swift and easy funnel installation and removal, even by female researchers.
- Stable center of gravity design minimizing vibration even with one sided sample installation or high speed tilted movement.




One-touch mechanism for convenient sample installation and removal.

Controller for convenience and safety in use

- Controller with display panel installed at a 20° angle, allowing good visibility even from the floor; ease of operation.
- Safety devices for protecting the user and the experiment (protecting the device from overcurrent, automatic resumption upon return of power supply after power failure).



Tilted controller for enhanced viewing angle.



Error alarm and status indicator.



More flexibility in experiment schedule

- LC Connected (mobile monitoring system) network for flexibility in experiment planning (option).
- Count-down timer (Max. 999 hr. 59 min.).



Real-time monitoring and control through LC Connected network (option).




Link to mobile monitoring system introduction video

Accessories

Cat. No.	Description
AAHQ1011K	LC GreenBox

Maximum number of holders that can be installed on each side by funnel capacity



Specification

Model	RS-2
Shaking system	
Motion type	Vertical & Inclined reciprocating (0 ~ 20°)
Speed range (rpm)	Vertical 30 to 300 / Inclined 30 to 250
Speed accuracy at 100rpm (\pm rpm)	1
Amplitude, recip. stroke length (mm)	40
Timer	999hr 59 min
Dimension	
Exterior (W x D x H, mm)	600 x 460 x 470
Minimum required space considering 20° tilt	900 x 460 x 670
Max. load per each side (kg)	5
Net weight (kg)	52
Electrical data & Ordering No.	
220V / 60Hz (A)	0.4
Cat. No.	AAH32025K
120V / 60Hz (A)	0.7
Cat. No.	AAH32023U

Type	Funnel capacity & quantity	Minimum rpm	Maximum rpm	
			0° use	20° use
Double sided use	2L x 2ea / 2L x 2ea	30	300	250
	2L + 1L / 2L + 1L	30	300	250
	2L / 2L	30	300	250
	1L / 1L	30	300	250
Single sided use	2L x 2ea	50	300	250
	2L + 1L	40	300	250
	2L	30	300	250
	1L	30	300	250

Lab Companion Shaker, Stirrer & Mixer



Shaker, dual action

- Selection between rotation and reciprocation.
- Powerful mixing action with BLDC motor.



Shaker, general type

- Stable mixing at high loads with DD motor.



Shaker, program type

- User convenience with program control mode.



Shaker, compact type

- Compact design allowing use within 2-60°C chamber.



Microplate shaker

- Mixing of samples in microplates and microtubes.



Rocking/Waving shaker

- Tilt adjustment and count-down timer to increase convenience.



Rotator

- 2-tier loading of disks up to 120 * 1.5 ml disks.



Overhead stirrer

- Powerful torque motor.
- Overheating/overheating prevention safety feature.



Hotplate & Magnetic stirrer

- Recessed heater for rapid heating.
- Multiple safety devices to protect user and equipment.



Magnetic stirrer

- Stability even at high speed mixing
- Slip prevention cover.



Magnetic stirrer, multi type

- Adjustable mixing speed and timer setting by position.
- Models with heating function available.



Vortex mixer

- Low center of gravity design for stable operation.
- Wide range of accessories.

Lab Companion Korea

Head office & factory

Add. 153, Techno 2-ro, Yuseong-gu, Daejeon, 34025, South Korea

International sales office

Add. 10F-1005, 219, Gasandigital 1-ro, Geumcheon-gu, Seoul, 08501, South Korea

Tel. +82 2 2627 3816

Fax +82 2 3143 1824

E-mail overseas@jeiotech.com

Lab Companion U.S.A. - Jeio Tech, Inc.

Add. 19 Alexander Road, Ste. 7, Billerica, MA 01821-5094, U.S.A.

Tel. +1 781 376 0700 Fax +1 781 376 0704

E-mail info@jeiotech.com

Your best business partner

